

**DOUBLE ACTING
PNEUMATIC ACTUATOR**
**ÇİFT ETKİLİ
PNÖMATİK AKTÜATÖR**

DemirVana

**Basınç / Pressure : Min. 4 Bar
Max. 8 Bar**
Sıcaklık / Temp : Max. 80°C



	Model	Φ	Max. Output
	Number		Torque @5 Bar
1	DA-52	52	20.2 Nm
2	DA-63	63	35.5 Nm
3	DA-75	75	50.3 Nm
4	DA-83	83	77.1 Nm
5	DA-92	92	113.6 Nm
6	DA-105	105	164.4 Nm
7	DA-125	125	256 Nm
8	DA-140	140	
9	DA-160	160	668 Nm
10	DA-190	190	
11	DA-210	210	1316 Nm
12	DA-240	240	
13	DA-270	270	
14	DA-300	300	
15	DA-350	350	
16	DA-400	400	



Demir Vana ve Kontrol Elemanları Makina San. Tic. Ltd. Şti

Merkez Ofis : İkitelli OSB Pik Dökümcüler San.Sit CA Blok No:3 Başakşehir/İstanbul

Tel : +90 212 297 57 30 Fax : +90 212 297 57 33 E-mail : dv@demirvana.com Web: www.demirvana.com